

The following technical datasheet is provided by Adesiv.

For further information please either give us a call or visit the manufacturer's website.

Wood Floors and Accessories cannot be held liable for the information contained within this document.

All information is correct at the time of download from the manufacturer.



ADHESIVES FOR WOOD FLOORS



ADEGLOSS 10

MOISTURE-CURING EXPANDING POLYURETHANE RESIN

Moisture-curing resin that can be used both before and after sanding the parquet for small repairs of strips that are not bonded perfectly to the sub-floor.

TECHNICAL CHARACTERISTICS:

- Excellent expansion properties
- Solvent-free
- Excellent adhesive power

WHERE IT CAN BE APPLIED:

- Old wood flooring
- Pre-finished floors
- Unfinished floors

DO NOT USE:

- On exteriors
- To lay flooring

SPECIFIC CHARACTERISTICS (normal conditions):

Appearance:	Viscous liquid				
Colour:	Brown				
Brookfield viscosity at 20 °C (mPa*s):	4000 - 5000				
Yield:	Depending on use and thickness				
Working life (minutes):	10 - 15				
Usage temperature (°C):	+10 - +30				
Ready for walking on (hours):	3 - 4				
Film setting (hours):	12 - 24 hours (depending on use and thickness applied)				
Application/Equipment:	Special dropper (syringe)				
Equipment cleaning:	SOLVENTE GR7 solvent, before the product sets				
Storage (months): temperature between +5 °C and +25 °C	6				
Disposal information:	Dispose of in compliance with the local and national regulations in force				
Packaging:	250 ml containers with spout. Boxes of 20.				
Usage limitations:	Allow the product to reach room temperature of 20 °C before application. Frost sensitive Once the product has been opened, it will begin to set naturally Always use suitable personal protective equipment Always consult the technical and safety information sheets				

SURFACE PREPARATION:

Make a small hole on the panel where it is not securely bonded.

APPLICATION:

Allow the product to reach room temperature before use. Apply 2-3 drops of water underneath the wooden pieces being secured, preferably at the joint. After 2 minutes, add a small dose of ADEGLOSS 10 in the same place. Be careful not to use too much ADEGLOSS 10, as it swells significantly during the setting phase. ADEGLOSS 10 is a product that adheres strongly to varnish. For this reason, leakage of the product from cracks, which will result in damage to the surface being treated, must absolutely be avoided. Ambient temperature between 15 °C to 25 °C, relative humidity no greater than 75%. Always use suitable personal protective equipment. Always consult the technical and safety data sheet for the product.

HAZARD PICTOGRAMS:







ADEGLOSS 10- ADEGLOSS 10

Revision nr. 8

Dated 07/07/2017

Printed on 07/07/2017

Page n. 1/13

Safety data sheet

SECTION 1. Identification of the substance/mixture and of the company/undertaking.

1.1. Product identifier.

Code: ADEGLOSS 10 Product name. ADEGLOSS 10

1.2. Relevant identified uses of the substance or mixture and uses advised against. Intended use. Hygro-hardening expanding polyurethane resin.

For professional use.

1.3. Details of the supplier of the safety data sheet.

Name. Adesiv s.r.l.
Full address. Via Delle Rose, 31

District and Country. 36061 Bassano del Grappa (Vicenza)

Italia

Tel. 0424 566406 Fax. 0424 566473

e-mail address of the competent person

responsible for the Safety Data Sheet. laboratorio@adesiv.it

1.4. Emergency telephone number.

For urgent inquiries refer to. Poison centres (24/24 h)

Italy: +39 02 6610 1029 Germany: +49 30 192 40 UK: +44 844 892 0111 France: +33 (0) 1 40 05 48 48 Spain: +34 91 562 0420 Russia: +7 495 628 1687

SECTION 2. Hazards identification.

2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Suspected of causing cancer

Hazard classification and indication: Carcinogenicity, category 2

			e deposited of eddeling edition.	
Acute	toxicity, category 4	H332	Harmful if inhaled.	
Specif	ic target organ toxicity - repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated	i
			exposure.	
Eye irr	itation, category 2	H319	Causes serious eye irritation.	
Skin ir	ritation, category 2	H315	Causes skin irritation.	
Specif	ic target organ toxicity - single exposure, category 3	H335	May cause respiratory irritation.	
	atory sensitization, category 1	H334	May cause allergy or asthma symptoms or breathing	
Skin ir Specif	ritation, category 2 ic target organ toxicity - single exposure, category 3	H315 H335	Causes skin irritation. May cause respiratory irritation.	g

H351

difficulties if inhaled.
Skin sensitization, category 1 H317 May cause an allergic skin reaction.



Revision nr. 8

Dated 07/07/2017

Printed on 07/07/2017

Page n. 2/13

ADEGLOSS 10- ADEGLOSS 10

2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:





Signal words: Danger

Hazard statements:

H351 Suspected of causing cancer.

H332 Harmful if inhaled.

H373 May cause damage to organs through prolonged or repeated exposure.

H319 Causes serious eye irritation.
H315 Causes skin irritation.

H335 May cause respiratory irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

EUH204 Contains isocyanates. May produce an allergic reaction.

Precautionary statements:

P201 Obtain special instructions before use.

P280 Wear protective gloves / clothing and eye / face protection.
P284 [In case of inadequate ventilation] wear respiratory protection.

P304+P340 IF INHALED: remove person to fresh air and keep comfortable for breathing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

Contains: 4,4'-methylenediphenyl diisocyanate

Diphenylmethandiisocyanate, isomers and homologues

Isocyanic acid, polymethylenepolyphenylene ester, polymer with α-hydro-ω.-hydroxypolyoxy(methyl-1,2-ethanediyl)

Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl)phenyl isocyanate / methylene diphenyl

diisocyanate

2.3. Other hazards.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients.

3.2. Mixtures.

Contains:

The full wording of hazard (H) phrases is given in section 16 of the sheet.

Identification. Concentration, % Classification 1272/2008 SCLs



Revision nr. 8

Page n. 3/13

Dated 07/07/2017

Printed on 07/07/2017

ADEGLOSS 10- ADEGLOSS 10

(CLP).

Isocyanic acid, polymethylenepolyphenylene ester, polymer with α-hydro-ω.hydroxypolyoxy(methyl-1,2-ethanediyl)

CAS. 53862-89-8 30 - 60

Carc. 2 H351, Acute Tox. 4 H332, STOT RE 2 H373, Eye

Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Resp. Sens. 1 H334, Skin

Sens. 1 H317

EC. -

INDEX. -

Diphenylmethandiisocyanate, isomers and

homologues

CAS. 9016-87-9 30 - 60

EC. -

INDEX. 615-005-00-9

4,4'-methylenediphenyl diisocyanate

CAS. 101-68-8

7 - 13

EC. 202-966-0 INDEX. 615-005-00-9

Reg. no. 01-2119457014-47-XXXX

Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl)phenyl

isocyanate / methylene diphenyl diisocyanate

CAS. -

1 - 3

Carc. 2 H351, Acute Tox. 4

H332, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Resp. Sens. 1 H334, Skin

Sens. 1 H317

Not applicable.

Not applicable.

Carc. 2 H351, Acute Tox. 4 H332, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2

H315, STOT SE 3 H335, Resp. Sens. 1 H334, Skin

Sens. 1 H317

Carc. 2 H351, Acute Tox. 4

H332, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335,

Resp. Sens. 1 H334, Skin

Sens. 1 H317

STOT SE 3; H335: C ≥ 5 %

Eye Irrit. 2; H319: C ≥ 5 %

Skin Irrit. 2; H315: C ≥ 5 %

Resp. Sens. 1; H334: C ≥ 0,1

Not applicable.

EC. 905-806-4 INDEX. -

Reg. no. 01-2119457015-45-XXXX

SECTION 4. First aid measures.

4.1. Description of first aid measures.

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists,

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.



Revision nr. 8

Dated 07/07/2017

Printed on 07/07/2017

Page n. 4/13

ADEGLOSS 10- ADEGLOSS 10

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed.

Specific information on symptoms and effects caused by the product are unknown. For symptoms and effects caused by the contained substances, see chap. 11.

4.3. Indication of any immediate medical attention and special treatment needed.

Information not available.

SECTION 5. Firefighting measures.

5.1. Extinguishing media.

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture.

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

5.3. Advice for firefighters.

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures.

6.1. Personal precautions, protective equipment and emergency procedures.

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions.

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up.

Collect the leaked product into a suitable container. If the product is flammable, use explosion-proof equipment. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections.

Any information on personal protection and disposal is given in sections 8 and 13.



ADEGLOSS 10- ADEGLOSS 10

Revision nr. 8

Dated 07/07/2017

Printed on 07/07/2017

Page n. 5/13

SECTION 7. Handling and storage.

7.1. Precautions for safe handling.

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities.

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s).

Information not available.

SECTION 8. Exposure controls/personal protection.

8.1. Control parameters.

Regulatory References:

DEU	Deutschland	MAK-und BAT-Werte-Liste 2012

DNK Danmark Graensevaerdier per stoffer og materialer

ESP España INSHT - Límites de exposición profesional para agentes químicos en

España 2015

FRA France JORF n°0109 du 10 mai 2012 page 8773 texte n° 102

HUN Magyarország 50/2011. (XII. 22.) NGM rendelet a munkahelyek kémiai biztonságáról POL Polska ROZPORZĄDZENIE MINISTRA PRACY I POLITYKI SPOŁECZNEJ z dnia

16 grudnia 2011r

4,4'-methylenediphenyl diis	ocyanate							
Threshold Limit Value.								
Type	Country	TWA/8h		STEL/15min				
		mg/m3	ppm	mg/m3	ppm			
			PP		PP			
AGW	DEU	0,05		0,05				
TLV	DNK	0,05	0,005	0,1	0,01			
VLA	ESP	0,052	0,005					
VLEP	FRA	0,1	0,01	0,2	0,02			
AK	HUN	0,05		0,05				
NDS	POL	0,05		0,2				
Predicted no-effect concentration	- PNEC.							
Normal value in fresh water				1		mg/l		
Normal value in marine water			0,1		mg/l			
Normal value for water, intermitte			10		mg/l			
Normal value of STP microorganisms				1		mg/l		
Normal value for the terrestrial compartment			1		mg/k	g/d		
Health - Derived no-effect le	evel - DNEL / [OMEL						
Effects on					Effects on			
	consumers.				workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral.		20 mg/kg		.,		- 1		,



Revision nr. 8

Dated 07/07/2017 Printed on 07/07/2017

Page n. 6/13

ADEGLOSS 10- ADEGLOSS 10

Inhalation Skin.

0.05 mg/m3 17,2 mg/cm2 $0.05 \, \text{mg/m}^{3}$ 25 mg/kg bw 0.025 mg/m3 0.025 mg/m3 0,1 mg/m3 28,7 mg/cm2 $0.1 \, \text{mg/m}3$ 50 mg/kg bw 0.05 ma/m3

0.05 mg/m3

Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl)phenyl isocyanate / methylene diphenyl diisocyanate

Predicted no-effect concentration - PNEC.

Normal value in fresh water mg/l Normal value in marine water ma/l Normal value of STP microorganisms ma/l Normal value for the terrestrial compartment mg/kg

Health - Derived no-effect level - DNEL / DMEL

1	nealth - Derived no-effect level - DNEL / DIVIEL								
		Effects on consumers.				Effects on workers			
	Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
	Oral.		20 mg/kg bw/d						
	Inhalation. Skin.	0,05 mg/m3 17,2 mg/cm2	0,05 mg/m3 25 mg/kg bw/d	0,025 mg/m3	0,025 mg/m3	0,1 mg/m3 28,7 mg/cm2	0,1 mg/m3	0,05 mg/m3	0,05 mg/m3

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

SAMPLING METHODS (IFA-GESTIS):

4,4'-methylenediphenyl diisocyanate

http://amcaw.ifa.dguv.de/substance/methoden/007-L-MDI.pdf

8.2. Exposure controls.

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

FYF PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type B filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear



Revision nr. 8

Dated 07/07/2017

Printed on 07/07/2017

Page n. 7/13

ADEGLOSS 10- ADEGLOSS 10

open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS.

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties.

9.1. Information on basic physical and chemical properties.

Appearance liquid Colour brown Odour acrid Not available. Odour threshold. Not available. pH. Melting point / freezing point. Not available. Initial boiling point. 368 °C. Boiling range. Not available. 225 °C. Flash point. **Evaporation Rate** Not available. Flammability of solids and gases Not available. Lower inflammability limit. Not available. Upper inflammability limit. Not available. Lower explosive limit. Not available. Upper explosive limit. Not available. Vapour pressure. Not available. Vapour density Not available. Relative density. 1.15 kg/l @ 20°C Solubility Not available. Partition coefficient: n-octanol/water Not available.

Auto-ignition temperature. Not available. Decomposition temperature. Not available.

Viscosity 2350 – 3350 mPa*s (#3, 20 rpm) @ 25°C. Explosive properties Not available.

Oxidising properties Not available.

9.2. Other information.

Information not available.

SECTION 10. Stability and reactivity.

10.1. Reactivity.

4,4'-methylenediphenyl diisocyanate

May react dangerously if exposed to: water, alcohols, amines, strong bases.

10.2. Chemical stability.

Information not available.

10.3. Possibility of hazardous reactions.

The product may react violently with water.

10.4. Conditions to avoid.



Revision nr. 8

Dated 07/07/2017

Printed on 07/07/2017

Page n. 8/13

ADEGLOSS 10- ADEGLOSS 10

Avoid overheating. Prevent moisture or water from penetrating inside the containers.

10.5. Incompatible materials.

Information not available.

10.6. Hazardous decomposition products.

Information not available.

SECTION 11. Toxicological information.

11.1. Information on toxicological effects.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

ACUTE TOXICITY.

LC50 (Inhalation - vapours) of the mixture:12,64 mg/l

LC50 (Inhalation - mists / powders) of the mixture:11,5 mg/l

LD50 (Oral) of the mixture: Not classified (no significant component).

LD50 (Dermal) of the mixture: Not classified (no significant component).

4,4'-methylenediphenyl diisocyanate

LD50 (Oral) > 10000 mg/kg rat

LD50 (Dermal) > 9400 mg/kg rabbit

LC50 (Inhalation) 1,5 mg/l/4h rat

Diphenylmethandiisocyanate, isomers and homologues

LD50 (Oral) > 10000 mg/kg rat

LD50 (Dermal) > 9400 mg/kg rabbit

LC50 (Inhalation) 0,31 mg/l/4h rat

Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl)phenyl isocyanate / methylene diphenyl diisocyanate

LD50 (Oral) > 10000 mg/kg rat

LD50 (Dermal) > 9400 mg/kg rabbit

LC50 (Inhalation) 0,49 mg/l/4h rat

SKIN CORROSION / IRRITATION.

Causes skin irritation.

SERIOUS EYE DAMAGE / IRRITATION.

Causes serious eye irritation.

RESPIRATORY OR SKIN SENSITISATION.

Sensitising for the skin.

GERM CELL MUTAGENICITY.

Does not meet the classification criteria for this hazard class.

CARCINOGENICITY.

Suspected of causing cancer.

REPRODUCTIVE TÖXICITY.

Does not meet the classification criteria for this hazard class.

STOT - SINGLE EXPOSURE.

May cause respiratory irritation.

STÓT - REPEÄTED ÉXPOSURE.

May cause damage to organs.

ASPIRATION HAZARD.



Revision nr. 8

Dated 07/07/2017

Printed on 07/07/2017

Page n. 9/13

ADEGLOSS 10- ADEGLOSS 10

Does not meet the classification criteria for this hazard class.

SECTION 12. Ecological information.

12.1. Toxicity.

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

> 1640 mg/l/72h Desmodesmus Subspicatus

4,4'-methylenediphenyl

diisocyanate

 $LC50^{'}$ - for Fish. > 1000 mg/l/96h Danio Rerio EC50 - for Crustacea. > 1000 mg/l/48h Daphnia Magna

EC50 - for Algae / Aquatic

Plants.

Chronic NOEC for > 10 mg/l (504 h)

Crustacea.

12.2. Persistence and degradability.

Diphenylmethandiisocyanate, isomers and homologues NOT rapidly biodegradable.

Reaction mass of 4,4'methylenediphenyl diisocyanate and o-(pisocyanatobenzyl)phenyl isocyanate / methylene diphenyl diisocyanate NOT rapidly biodegradable.

12.3. Bioaccumulative potential.

Reaction mass of 4,4'methylenediphenyl diisocyanate and o-(pisocyanatobenzyl)phenyl isocyanate / methylene diphenyl diisocyanate

Partition coefficient: n-octanol/water.

BCF. 4,51

200

12.4. Mobility in soil.

Information not available.

12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects.

Information not available.

SECTION 13. Disposal considerations.



Revision nr. 8

Dated 07/07/2017

Printed on 07/07/2017

Page n. 10/13

ADEGLOSS 10- ADEGLOSS 10

13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information.

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number.

Not applicable.

14.2. UN proper shipping name.

Not applicable.

14.3. Transport hazard class(es).

Not applicable.

14.4. Packing group.

Not applicable.

14.5. Environmental hazards.

Not applicable.

14.6. Special precautions for user.

Not applicable.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code.

Information not relevant.

SECTION 15. Regulatory information.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.

Seveso Category - Directive 2012/18/EC: None.

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

Product.

Point.

3



Revision nr. 8

Page n. 11/13

Dated 07/07/2017

Printed on 07/07/2017

ADEGLOSS 10- ADEGLOSS 10

Contained substance.

Point. 56 Diphenylmethandiiso

cyanate, isomers and

homologues

Point. 56 4,4'-

methylenediphenyl diisocyanate Reg. no.: 01-2119457014-47-XXXX

Substances in Candidate List (Art. 59 REACH).

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisarion (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment.

No chemical safety assessment has been processed for the mixture and the substances it contains.

SECTION 16. Other information.

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Carc. 2 Carcinogenicity, category 2

Acute Tox. 4 Acute toxicity, category 4

STOT RE 2 Specific target organ toxicity - repeated exposure, category 2

Eye Irrit. 2 Eye irritation, category 2
Skin Irrit. 2 Skin irritation, category 2

STOT SE 3 Specific target organ toxicity - single exposure, category 3

Resp. Sens. 1 Respiratory sensitization, category 1



Revision nr. 8

Dated 07/07/2017

Printed on 07/07/2017

Page n. 12/13

ADEGLOSS 10- ADEGLOSS 10

Skin Sens 1 Skin sensitization, category 1 H351 Suspected of causing cancer.

H332 Harmful if inhaled.

H373 May cause damage to organs through prolonged or repeated exposure.

H319 Causes serious eye irritation.

H315 Causes skin irritation.

H335 May cause respiratory irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

EUH204 Contains isocyanates. May produce an allergic reaction.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
- 4. Regulation (EU) 2015/830 of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website

Note for users:



Revision nr. 8

Dated 07/07/2017

Printed on 07/07/2017

Page n. 13/13

ADEGLOSS 10- ADEGLOSS 10

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.