



The following technical datasheet is provided by Loba.

For further information please either give us a call or visit the manufacturer's website.

Wood Floors and Accessories cannot be held liable for the information contained within this document.  
All information is correct at the time of download from the manufacturer.

---

Spilsby Road • Harold Hill • Romford • RM3 8SB • **T** 020 8501 6730 • **E** [info@wfa.uk.net](mailto:info@wfa.uk.net) • **W** [www.wfa.uk.net](http://www.wfa.uk.net)

Registered in England under Company No: 03746590 VAT No: 765 9995 45

# TECHNICAL INFORMATION

## WS Life SEMI-GLOSS



### Sets new standards in his range

Waterborne 1-Component finish for wooden floors. For normal wear. Elastic, stable properties.




- Good price/performance ratio
- Balanced properties
- High filling capacity
- Simple and safe application

### Range of use:

Suitable for parquet and hardwood floors.



## Technical Data

<b>Art.-no.</b>			
11524	5 l 10 l	4 -	128 60
Gloss level approx.*	40		
Solids	29 ±2%		
Viscosity DIN 4	19 ±2s		
Storage and transportation	12 months of storage stability. No hazardous material according to ADR. Store and transport between +5 to +25°C. Protect from frost.		
GISCODE	W2+		
2004/42/CE	EU limit value for this product (cat. A/i): 140 g/l (2010). This product contains max. 49 g/l VOC.		

\* The degree of gloss is measured at 60° on glass. It depends on the layer thickness and ambient conditions (temp., rel. humidity) during the drying process. The values are intended merely as a guide.



### Application

---

- The surface must be sanded properly, wood moisture content max. 12%.
- The floor must be dry and free from any old coatings, oil, grease, wax, silicone, sanding dust and other contaminants. Room temperature +15°C to +25°C, relative humidity 40% to 75%, material temperature +18°C to +25°C. Ensure working areas are adequately ventilated.
- Transfer material to a LOBATOOL varnish bucket before applying.
- Shake the contents well.
- Observe the general and, if available, the product-specific health and safety instructions. More specific information relating to GISCODE can be found in the usage instructions, which are available at [www.wingis-online.de](http://www.wingis-online.de).

### Thinner

The product is supplied ready for use and must not be diluted!

### Application tool/application rate

LOBATOOL roller Deluxe 120 / 100-120 ml(g)/m<sup>2</sup> = 8-10m<sup>2</sup>/l(kg)

LOBATOOL roller Microfaser 100-120 / 80-100 ml(g)/m<sup>2</sup> = 10-12m<sup>2</sup>/l(kg)

### Intermediate sanding

Able to recoat without intermediate sanding within the first 24 hours. After this time, an intermediate sanding is necessary. An intermediate sanding before the last application will achieve an even finish. Use LOBATOOL perforated pad P120 or finer, alternatively Sanding Net P120 or finer. Carefully remove dust before overcoating.

### Drying time

- Earliest possible recoating after 4-6 hours.
- Careful use possible after 4-6 hours.
- Earliest possible intermediate sanding after 8-10 hours.
- Light use after 24 hours.
- Full use and covering possible after 5 days.
- The floor can be covered earlier by using LOBATOOL Cover 400, for details see the TI for the product.

### We recommend using a primer:

to minimise side bonding and to seal off wood constituents, e.g. in exotic timber.

- WS EasyPrime.
- OptiPrime.
- PrimaSeal Plus (contains solvent).

### Use on parquet and hardwood floors:

- Prepare and prime the substrate properly.
- Allow the primer to dry as specified.
- Apply by roller.
- Dry.
- Intermediate sanding.
- Apply second coating layer by roller.



### General guidelines

---

**Cleaning of tools:** Clean tools and equipment immediately with water.

**Drying time:** The indicated drying times are valid for +20°C and 55% to 65% relative humidity, and assume careful, draught-free ventilation of the working area. Lower temperatures, higher relative humidity or poorer ventilation lead to longer drying times. Do not apply any protective coverings, wet clean the surface or lay carpet until the coating has achieved its final hardening. Product-specific data can be found in the relevant technical information.

**Intermediate sanding:** Where several layers of coatings are applied, if any layer is not overcoated within 24 hours, then the only way to ensure adequate bond between the layers is by intermediate sanding. An intermediate sanding before the final application will achieve an even surface. Carefully clean off the dust after intermediate sanding.

**Use with or without a primer:** Generally all finishes can be used without a primer. The use of a primer increases application reliability and ensures a finish free of lap marks and stripes, almost irrespective of the wood type. Further details can be found in the LOBA wood type list in the current product catalogue.

**Edge bonding:** Waterborne coating systems usually show a tendency for edge bonding. Several measures can be taken to minimise the formation of irregular joints and the associated locking effect. The use of shear-resistant or permanently elastic adhesive to glue the parquet, careful filling of the joints with wood putty, use of suitable primers, such as LOBADUR WS EasyPrime, pretreatment of the groove sides on solid wood boards with wax compatible with the coating before laying. Taking steps to ensure that the room climate, in particular the relative humidity, remains constant. (Careful advising of the customer is recommended). Old floors with damaged, weak adhesives, and flexibly glued or nailed parquet, plank flooring, wood block flooring, industrial parquet, as well as parallel parquet, parquet on underfloor heating, and woods which change their moisture content quickly, such as beech and maple.

**Interactions:** Materials such as carpet underlays, furniture legs, castors, flexible adhesives used for parquet or for fixing can lead to softening and discolouration. Material building up in the joints can adversely affect touch and appearance. Exposure to hair dyes or rubber tyres on cars, motorcycles and cycles can lead to permanent, irreversible discolouration of the surface.

The information in this document and all other advice and recommendations that we provide to help and assist the applicator are based on previous experience and relate to Spezial conditions. Because of the wide range of possible uses and conditions of application of our products, we do not relieve users from the need to carry out their own trials or to seek technical advice by speaking to the LOBA application engineering department. Observe the floor covering manufacturer's recommendations and the provisions of the current standards. Our liabilities and responsibilities are exclusively in accordance with our Terms and Conditions and are not extended by this information or by our advice. The publishing of a new technical data sheet automatically invalidates the earlier version.

The words or symbols denoted by ® stand for trademark rights that are at least registered and protected in the territory of Germany.



# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 16.03.2018

Version number 5

Revision: 09.03.2018

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

· **Product name** LOBADUR WS Life glänzend, halbmatt, matt

· **Article number:** 115249

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

#### Application of the substance / the mixture

Dispersion paint/ Latex paint

Paint

Coating

#### 1.3 Details of the supplier of the safety data sheet

##### Manufacturer/Supplier:

LOBA GmbH & Co. KG

Leonberger Straße 56 - 62

D-71254 Ditzingen

Tel.: +49 (0)7156/357-0

##### Informing department:

Productmanagement

e-mail: [service@loba.de](mailto:service@loba.de)

#### 1.4 Emergency telephone number:

Germany: Giftnotruf Berlin, Tel. +49 (0)30 30686 790

International: INFOTRAC, Tel. +1 352 323 3500

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) No 1272/2008

The product is not classified according to the CLP regulation.

#### 2.2 Label elements

##### Labelling according to Regulation (EC) No 1272/2008 Void

· **Hazard pictograms** Void

· **Signal word** Void

· **Hazard statements** Void

##### Additional information:

EUH208 Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

EUH210 Safety data sheet available on request.

#### 2.3 Other hazards

##### Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

#### 3.2 Chemical characterisation: Mixtures

· **Description:** Mixture of the substances listed below with harmless additions.

##### Dangerous components:

CAS: 34590-94-8	(2-methoxymethylethoxy)propanol	2.5-5%
EINECS: 252-104-2	substance with a Community workplace exposure limit	

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

· **General information** No special measures required.

· **After inhalation** Supply fresh air; consult doctor in case of symptoms.

(Contd. on page 2)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 16.03.2018

Version number 5

Revision: 09.03.2018

**Product name** *LOBADUR WS Life glänzend, halbmatt, matt*

(Contd. of page 1)

- **After skin contact** *The product is not skin irritating.*
- **After eye contact** *Rinse opened eye for several minutes under running water.*
- **After swallowing** *In case of persistent symptoms consult doctor.*
- **4.2 Most important symptoms and effects, both acute and delayed** *No further relevant information available.*
- **4.3 Indication of any immediate medical attention and special treatment needed**  
*No further relevant information available.*

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** *Use fire fighting measures that suit the environment.*
- **5.2 Special hazards arising from the substance or mixture** *No further relevant information available.*
- **5.3 Advice for firefighters**
- **Protective equipment:** *No special measures required.*

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** *Not required.*
- **6.2 Environmental precautions:**  
*Do not allow product to reach sewage system or water bodies.*  
*Inform respective authorities in case product reaches water or sewage system.*
- **6.3 Methods and material for containment and cleaning up:**  
*Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).*
- **6.4 Reference to other sections**  
*See Section 7 for information on safe handling*  
*See Section 8 for information on personal protection equipment.*  
*See Section 13 for information on disposal.*

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** *No special measures required.*
- **Information about protection against explosions and fires:** *No special measures required.*
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** *No special requirements.*
- **Information about storage in one common storage facility:** *Not required.*
- **Further information about storage conditions:** *None.*
- **Storage class** *12*
- **7.3 Specific end use(s)** *No further relevant information available.*

### SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical systems:** *No further data; see item 7.*

#### 8.1 Control parameters

- **Components with critical values that require monitoring at the workplace:**

**34590-94-8 (2-methoxymethylethoxy)propanol**

WEL	Long-term value: 308 mg/m <sup>3</sup> , 50 ppm
Sk	

- **Additional information:** *The lists that were valid during the compilation were used as basis.*

(Contd. on page 3)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 16.03.2018

Version number 5

Revision: 09.03.2018

**Product name** *LOBADUR WS Life glänzend, halbmatt, matt*

(Contd. of page 2)

· **8.2 Exposure controls**

· **Personal protective equipment**

· **General protective and hygienic measures**

*The usual precautionary measures should be adhered to in handling the chemicals.*

· **Breathing equipment:** *Not required.*

· **Protection of hands:**

*The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.*

*Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation*

· **Material of gloves**

*Nitrile rubber, NBR*

*The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.*

*Recommended thickness of the material:  $\geq 0.4$  mm*

· **Penetration time of glove material**

*The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.*

*For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).*

*Value for the permeation: Level  $\leq 6$*

· **Eye protection:** *Safety glasses recommended during refilling.*

**SECTION 9: Physical and chemical properties**

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· <b>Form:</b>	<i>Fluid</i>
· <b>Colour:</b>	<i>Whitish</i>
· <b>Smell:</b>	<i>Recognisable</i>
· <b>Odour threshold:</b>	<i>Not determined.</i>

· **pH-value at 20 °C:** *7.5*

· **Change in condition**

· **Melting point/freezing point:** *Not determined*

· **Initial boiling point and boiling range:** *100 °C*

· **Flash point:** *Not applicable*

· **Inflammability (solid, gaseous)** *Not applicable.*

· **Ignition temperature:**

· **Decomposition temperature:** *Not determined.*

· **Self-inflammability:** *Product is not selfigniting.*

· **Explosive properties:** *Product is not explosive.*

· **Lower:** *Not determined.*

· **Upper:** *Not determined.*

· **Steam pressure:** *Not determined.*

· **Density at 20 °C** *1.04 g/cm<sup>3</sup>*

· **Relative density** *Not determined.*

· **Vapour density** *Not determined.*

· **Evaporation rate** *Not determined.*

(Contd. on page 4)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 16.03.2018

Version number 5

Revision: 09.03.2018

**Product name** *LOBADUR WS Life glänzend, halbmatt, matt*

(Contd. of page 3)

- |  |  |
|--|--|
| <b>· Solubility in / Miscibility with Water:</b> | Not miscible or difficult to mix           |
| <b>· Partition coefficient: n-octanol/water:</b> | Not determined.                            |
| <b>· Viscosity:</b>                              |  |
| <b>dynamic:</b>                                  | Not determined.                            |
| <b>kinematic at 20 °C:</b>                       | 20 s (ISO 4 mm)                            |
| <b>Organic solvents:</b>                         | 5.3 %                                      |
| <b>Water:</b>                                    | 0.8 %                                      |
| <b>· Solids content:</b>                         | 28.0 %                                     |
| <b>· 9.2 Other information</b>                   | No further relevant information available. |

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
*Water hazard class 1 (Self-assessment): slightly hazardous for water.  
 Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.*
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

(Contd. on page 5)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 16.03.2018

Version number 5

Revision: 09.03.2018

**Product name** *LOBADUR WS Life glänzend, halbmatt, matt*

(Contd. of page 4)

· **12.6 Other adverse effects** *No further relevant information available.*

### **SECTION 13: Disposal considerations**

· **13.1 Waste treatment methods**

· **Recommendation**

*After prior treatment product has to be landfilled or incinerated under adherence to the regulations pertaining to the disposal of especially hazardous waste.*

· **European waste catalogue**

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 12	waste paint and varnish other than those mentioned in 08 01 11

· **Uncleaned packagings:**

· **Recommendation:** *Disposal must be made according to official regulations.*

### **SECTION 14: Transport information**

· **14.1 UN-Number**

· **ADR, ADN, IMDG, IATA** *Void*

· **14.2 UN proper shipping name**

· **ADR, ADN, IMDG, IATA** *Void*

· **14.3 Transport hazard class(es)**

· **ADR, ADN, IMDG, IATA**

· **Class** *Void*

· **14.4 Packing group**

· **ADR, IMDG, IATA** *Void*

· **14.5 Environmental hazards:**

*Not applicable.*

· **14.6 Special precautions for user**

*Not applicable.*

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

*Not applicable.*

· **UN "Model Regulation":**

*Void*

### **SECTION 15: Regulatory information**

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** *None of the ingredients is listed.*

· **REGULATION (EC) No 1907/2006 ANNEX XVII** *Conditions of restriction: 65*

· **National regulations**

· **Water hazard class:** *Water hazard class 1 (Self-assessment): slightly hazardous for water.*

· **15.2 Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

### **SECTION 16: Other information**

*These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

(Contd. on page 6)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 16.03.2018

Version number 5

Revision: 09.03.2018

**Product name LOBADUR WS Life glänzend, halbmatt, matt**

(Contd. of page 5)

*Alteration in the context will be marked with a cross (\*).*

- **Department issuing data specification sheet:** Productmanagement.
- **Contact:** Dr W. Ehmann
- **Abbreviations and acronyms:**
  - ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*
  - IMDG: International Maritime Code for Dangerous Goods*
  - IATA: International Air Transport Association*
  - GHS: Globally Harmonised System of Classification and Labelling of Chemicals*
  - EINECS: European Inventory of Existing Commercial Chemical Substances*
  - ELINCS: European List of Notified Chemical Substances*
  - CAS: Chemical Abstracts Service (division of the American Chemical Society)*
  - PBT: Persistent, Bioaccumulative and Toxic*
  - vPvB: very Persistent and very Bioaccumulative*
- **\* Data compared to the previous version altered.**

GB