



The following technical datasheet is provided by Osmo.

For further information please either give us a call or visit the manufacturer's website.

Wood Floors and Accessories cannot be held liable for the information contained within this document.  
All information is correct at the time of download from the manufacturer.

---

Spilsby Road • Harold Hill • Romford • RM3 8SB • **T** 020 8501 6730 • **E** [info@wfa.uk.net](mailto:info@wfa.uk.net) • **W** [www.wfa.uk.net](http://www.wfa.uk.net)

Registered in England under Company No: 03746590 VAT No: 765 9995 45



## OIL STAIN

Especially for the professional colouring of wooden floors - seamless and individual!



3519 Natural  
transparent | intensive



3501 White  
transparent | intensive



3512 Silver Grey  
transparent | intensive



3514 Graphite  
transparent | intensive



3516 Jatoba  
transparent | intensive



3518 Light Grey  
transparent | intensive



3541 Havanna  
transparent | intensive



3543 Cognac  
transparent | intensive



3564 Tobacco  
transparent | intensive



3590 Black  
transparent | intensive



### PRODUCT DESCRIPTION

Transparent or intensive coloured base coat for all wooden floors and furniture. Osmo Oil Stain is stain-resistant, water-repellent and abrasion-resistant and results in a surface that is pleasant to the touch.

In comparison to conventional finishes, the use of plant ingredients creates a more even colour and more harmonious appearance. The necessary clear top coat is to be carried out with a Osmo Polyx®-Oil. Suitable for wood; microporous surface will not crack, peel, flake or blister. Resistant against wine, beer, cola, coffee, tea, fruit juice, milk and water in accordance with German DIN 68861-1A – no water spots.

The dry finish is safe for humans, animals and plants (resistant to saliva and perspiration acc. German DIN 53160, suitable for children's toys acc. EN 71.3).

### RECOMMENDED USE

Osmo Oil Stain is ideal as a coloured base coat for all wooden floors, such as solid wood, plank, strip, OSB and cork flooring, as well as stairs and furniture surfaces.

### INGREDIENTS

Based on natural plant oils (sunflower oil, soya oil, linseed oil and thistle oil), iron oxide and organic pigments, titanium dioxide white pigment, siccatives (drying agents) and water-repellent additives. Deaeromatized white spirit (benzene-free). EU limit value for this product (cat. A/i): 500 g/l VOC (2010). This product contains max. 500 g/l VOC. Detailed declaration of ingredients available upon request.

### TECHNICAL DATA

Specific gravity: 0.9-1.15 g/cm<sup>3</sup>

Viscosity: 30-50s DIN 53211/4 mm

Odour: faint/mild, after drying odourless

Flashpoint: >60°C acc. DIN EN ISO 2719

### STORAGE

Up to 5 years and longer if can is kept dry and closed tightly. If thickened by frost, store for 24-36 hours at room temperature before use.

### SURFACE PREPARATION

Wood surface must be clean, dry and frost-free (moisture content max. 18%).

Osmo Oil Stain is ready to use. Do not thin. Stir well before use.

Clean old microporous stains thoroughly. Old paints and lacquers must be completely removed. As a general rule, wear a dust mask during sanding works. Fill small cracks, larger joints or holes in wood (with Osmo Wood Filler).

Sand wood surfaces carefully. Begin with coarse sandpaper – final sanding work for flooring grit P120-150, for furniture grit P220-240. Before oiling the surface, remove sanding dust with a broom or vacuum.

The finished surface is influenced by several factors, including the condition of the wood. Therefore, a trial application is always required, especially for unfamiliar surfaces.



## METHODS OF APPLICATION

Transparent colour: with Osmo Floor Brush, Microfibre Roller, Oil Finish Applicator Fleece (Hand Pad Holder) or Double Blade Scraper, apply very thinly and evenly to the clean and dry wood along the wood grain and rub into the wood with a white pad. Allow to dry for approx. 12 hours under good ventilation.

Intensive colour: if a stronger colour is desired, apply thinly along the wood grain with Osmo Microfibre Roller or Floor Brush, and spread well.

Tip: With an unused Microfibre Roller, any brush-strokes can be removed within 30 minutes after application. Ventilate well while drying. If an even more intensive colour is desired, apply a second coat with Osmo Double Blade Scraper, Microfibre Roller or Floor Brush, and rub into the wood with a white pad.

After thoroughly drying, a top coat should be carried out with a clear Osmo Polyx®-Oil.

For smaller areas, e.g. furniture, Osmo Oil Stain can be applied with a lint-free cloth.

## CLEANING OF TOOLS

With Osmo Brush Cleaner (free of aromatic compounds).

## DRYING TIME

Approx. 12 hours (normal climatic conditions, 23 °C/ 50 % rel. humidity). Lower temperatures and/or higher air humidity can increase the drying time. Ventilate well while drying.

## COVERAGE

1 litre covers approx. 24-48 m<sup>2</sup> with one coat. Coverage depends significantly on the condition of the wood. All information refers to smooth and planed/sanded surfaces. Other surfaces may lead to differences in coverage.

## NOTE

Applications with the Hardener for Oil Stain 6631 as drying accelerator are also possible as an option. Please observe the instructions for a correct application.

For dark woods and hardwoods rich in extractives (e.g. Wenge, Merbau, Jatoba etc.), we recommend using Osmo Wood Wax Finish Clear Extra Thin or Osmo Polyx®-Oil 2K Pure. A trial application is recommended.

Colour tone 3501 White: An intensive white surface is not recommended for flooring because it is more sensitive and prone to natural yellowing. As a top coat for such surfaces, the pigmented Polyx®-Oils 3040 or 3240 (White transparent) is recommended.

Colour tone 3519 Natural: A thin coat is recommended either with Osmo Microfibre Roller or Floor Brush. After drying, a coat with a clear Osmo Polyx®-Oil should be carried out. The natural colour tone of wood is preserved – it does not enhance the tone of wood, no permanent wet effect. This finish leaves white streaks on red/dark wood species.

## CAUTION

Keep out of reach of children. Do not get in eyes, on skin, or on clothing. If medical advice is needed, have product container or label at hand. Use only outdoors or in a well-ventilated area. Warning: Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition). The dried finish is classified as B2 (normal flammability) according to DIN 4102 regulations. Safety data sheet available on request.

## DISPOSAL

Dispose of leftover product and completely emptied packaging according to local official guidelines (waste code number 08 01 11). Only completely emptied cans can be recycled.

## COLOUR TONES

3501 White  
3512 Silver Grey  
3514 Graphite  
3516 Jatoba  
3518 Light Grey  
3519 Natural  
3541 Havanna  
3543 Cognac  
3564 Tobacco  
3590 Black

## CAN SIZES

0.50 L; 1 L; 2.50 L

The above mentioned information is provided to the best of our knowledge however without any liability.

Version 02/18

**Material Safety Data Sheets**  
 according to 1907/2006/EC, Article 31

Printing date 23.05.2018

Version number 2

Revision: 13.12.2017

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Trade name:** **Osmo Oil Stain**

**Article number:** 3501, 3512, 3514, 3516, 3518, 3519, 3541, 3543, 3564, 3590

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**advised against** No further relevant information available.

**Application of the substance / the mixture** Priming  
 Coating compound/ Surface coating/ paint

#### 1.3 Details of the supplier of the safety data sheet

**Manufacturer/Supplier:** Osmo Holz und Color GmbH & Co. KG  
 Affhüppen Esch 12  
 D-48231 Warendorf

#### Further information obtainable from:

Product safety department  
 Phone: +49 (0) 251 / 692 - 188  
 Fax: +49 (0) 251 / 692 - 462  
 e-mail: helmut.starp@osmo.de

#### 1.4 Emergency telephone number:

emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in German and English

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) No 1272/2008** The product is not classified, according to the CLP regulation.

#### 2.2 Label elements

##### Labelling according to Regulation

**(EC) No 1272/2008** Void

**Hazard pictograms** Void

**Signal word** Void

**Hazard statements** Void

##### Precautionary statements

Keep out of reach of children.  
 If medical advice is needed, have product container or label at hand.  
 P262 Do not get in eyes, on skin, or on clothing.  
 P271 Use only outdoors or in a well-ventilated area.

##### Additional information:

Observe the general safety regulations when handling chemicals.  
 Always wear a dust mask when sanding.  
 Safety data sheet available on request.

#### 2.3 Other hazards

Warning:  
 Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition)

(Contd. on page 2)

**Material Safety Data Sheets**  
 according to 1907/2006/EC, Article 31

Printing date 23.05.2018

Version number 2

Revision: 13.12.2017


**Trade name: Osmo Oil Stain**

(Contd. of page 1)

**Results of PBT and vPvB assessment**

**PBT:** Not applicable.  
**vPvB:** Not applicable.

**SECTION 3: Composition/information on ingredients****3.2 Mixtures****Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous components:**

EC number: 918-481-9	aliphatic hydrocarbons, C10-C13	 Asp. Tox. 1, H304	25-50%
Index number: 649-327-00-6			
Reg.nr.: 01-2119457273-39			

**Additional information:** The content of Titanium dioxide varies according to the colour shade.  
 For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures****4.1 Description of first aid measures**

**General information:** Immediately remove any clothing soiled by the product.  
 Take affected persons out into the fresh air.

**After inhalation:** Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.  
 In case of unconsciousness place patient stably in side position for transportation.

**After skin contact:** Immediately wash with water and soap and rinse thoroughly.  
 If skin irritation continues, consult a doctor.

**After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

**After swallowing:** If swallowed, seek medical advice immediately and show this container or label.

**4.2 Most important symptoms and effects, both acute and delayed**

Dizziness  
 Headache

**4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

**SECTION 5: Firefighting measures****5.1 Extinguishing media****Suitable extinguishing agents:** CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.**For safety reasons unsuitable extinguishing agents:**

Water with full jet

(Contd. on page 3)

**Material Safety Data Sheets**  
 according to 1907/2006/EC, Article 31

Printing date 23.05.2018

Version number 2

Revision: 13.12.2017

**Trade name: Osmo Oil Stain**

(Contd. of page 2)

**5.2 Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

**5.3 Advice for firefighters****Protective equipment:**

Mouth respiratory protective device.

**Additional information**

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**Ensure adequate ventilation  
Keep away from ignition sources.**6.2 Environmental precautions:**Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.**6.3 Methods and material for containment and cleaning up:**Warm water and cleansing agent  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).**6.4 Reference to other sections**See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.**SECTION 7: Handling and storage****7.1 Precautions for safe handling**Keep away from heat and direct sunlight.  
Use only in well ventilated areas.  
Keep receptacles tightly sealed.  
Prevent formation of aerosols.**Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

**7.2 Conditions for safe storage, including any incompatibilities****Storage:****Requirements to be met by storerooms and receptacles:**Store only in the original receptacle.  
Store in a cool location.**Information about storage in one common storage facility:**Do not store together with alkalis (caustic solutions).  
Do not store together with oxidising and acidic materials.**Further information about storage conditions:**Store in cool, dry conditions in well sealed receptacles.  
Keep container tightly sealed.**Storage class:**

10

(Contd. on page 4)

**Trade name: Osmo Oil Stain**

(Contd. of page 3)

7.3 *Specific end use(s)*

No further relevant information available.

### **SECTION 8: Exposure controls/personal protection**

**Additional information about design of technical facilities:**

No further data; see item 7.

#### **8.1 Control parameters**

**Ingredients with limit values that require monitoring at the workplace:**

**aliphatic hydrocarbons, C10-C13**

TWA (8 H)	Long-term value: 1,000 mg/m <sup>3</sup> , 150 ppm ppm
	Source: UK SIA

**Additional information:**

The lists valid during the making were used as basis.

#### **8.2 Exposure controls**

**Personal protective equipment:**

**General protective and hygienic measures:**

Immediately remove all soiled and contaminated clothing  
Avoid contact with the eyes and skin.  
Do not eat, drink, smoke or sniff while working.  
Do not carry product impregnated cleaning cloths in trouser pockets.

**Respiratory protection:**

Not necessary if room is well-ventilated.  
Use suitable respiratory protective device only when aerosol or mist is formed.  
Short term filter device:  
Gas filter EN 14387 Type A (organic gas / vapor (boiling point > 65 ° C)).

**Protection of hands:**

Protective gloves  
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
To avoid skin problems reduce the wearing of gloves to the required minimum.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**Material of gloves**

Nitrile rubber, NBR

**Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**For the permanent contact gloves made of the following materials are suitable:**

Nitrile rubber, NBR

**For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

Nitrile rubber, NBR

**Eye protection:**

Goggles recommended during refilling

(Contd. on page 5)

**Material Safety Data Sheets**  
 according to 1907/2006/EC, Article 31

Printing date 23.05.2018

Version number 2

Revision: 13.12.2017

**Trade name: Osmo Oil Stain****Body protection:** Protective work clothing

(Contd. of page 4)

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties****General Information****Appearance:**

<b>Form:</b>	Viscous
<b>Colour:</b>	Different according to colouring
<b>Odour:</b>	Mild

**Change in condition**

<b>Melting point/freezing point:</b>	Undetermined.
<b>Initial boiling point and boiling range:</b>	> 180 °C

**Flash point:** > 60 °C (DIN 53213)**Ignition temperature:** 240 °C**Auto-ignition temperature:** Product is not selfigniting.**Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.**Explosion limits:**

<b>Lower:</b>	0.7 Vol %
<b>Upper:</b>	6.0 Vol %

**Density at 20 °C:** 0.90 - 1.15 g/cm<sup>3</sup> (DIN 51757)**Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

**Viscosity:**

<b>Dynamic:</b>	Not determined.
<b>Kinematic at 20 °C:</b>	30-45 s (DIN 53211/4 mm)

**9.2 Other information** No further relevant information available.**SECTION 10: Stability and reactivity****10.1 Reactivity** No further relevant information available.**10.2 Chemical stability****Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

**10.3 Possibility of hazardous reactions**

Reacts with fabric soaked in the product (e.g. cleaning wool).

**10.4 Conditions to avoid**

No further relevant information available.

(Contd. on page 6)



**Material Safety Data Sheets**  
 according to 1907/2006/EC, Article 31

Printing date 23.05.2018

Version number 2

Revision: 13.12.2017

**Trade name: Osmo Oil Stain**

(Contd. of page 5)

**10.5 Incompatible materials:** No further relevant information available.**10.6 Hazardous decomposition products:**Carbon monoxide and carbon dioxide  
Nitrogen oxides (NOx)**Additional information:**

Warning:

Wash out any used cloth impregnated with this product immediately after use or store in an airtight container (danger of self-ignition)

**SECTION 11: Toxicological information****11.1 Information on toxicological effects****Acute toxicity** Based on available data, the classification criteria are not met.**LD/LC50 values relevant for classification:****aliphatic hydrocarbons, C10-C13**

Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>5,000 mg/kg (rat) (OECD 402)
Inhalative	LC50 / 4h	21 mg/l (rat) (OECD 403)

**13463-67-7 titanium dioxide**

Oral	LD50	>20,000 mg/kg (rat)
Dermal	LD50	>10,000 mg/kg (rabbit)

**Primary irritant effect:****Skin corrosion/irritation** At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.**Serious eye damage/irritation** Based on available data, the classification criteria are not met.**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.**CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)****Germ cell mutagenicity** Based on available data, the classification criteria are not met.**Carcinogenicity** Based on available data, the classification criteria are not met.**Reproductive toxicity** Based on available data, the classification criteria are not met.**STOT-single exposure** Based on available data, the classification criteria are not met.**STOT-repeated exposure** Based on available data, the classification criteria are not met.**Aspiration hazard** Based on available data, the classification criteria are not met.**SECTION 12: Ecological information****12.1 Toxicity****Aquatic toxicity:****aliphatic hydrocarbons, C10-C13**

EC50 / 48h	>1,000 mg/l (daphnia) (OECD 202)
------------	----------------------------------

(Contd. on page 7)

**Trade name: Osmo Oil Stain**

(Contd. of page 6)

EC50/ 72h	>1,000 mg/l (algae) (OECD 201)
LC50 / 96h	>1,000 mg/l (fish) (OECD 203)
Biolog. Abbaubarkeit	% (leicht abbaubar)

**12.2 Persistence and degradability** No further relevant information available.**12.3 Bioaccumulative potential** No further relevant information available.**12.4 Mobility in soil** No further relevant information available.**Additional ecological information:****General notes:** Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water**12.5 Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**12.6 Other adverse effects** No further relevant information available.**SECTION 13: Disposal considerations****13.1 Waste treatment methods****Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.**European waste catalogue**

08 01 19*	aqueous suspensions containing paint or varnish containing organic solvents or other dangerous substances
15 01 10*	packaging containing residues of or contaminated by dangerous substances

**Uncleaned packaging:****Recommendation:** Disposal must be made according to official regulations.**SECTION 14: Transport information****14.1 UN-Number****ADR, ADN, IMDG, IATA** Void**14.2 UN proper shipping name****ADR, ADN, IMDG, IATA** Void**14.3 Transport hazard class(es)****ADR, ADN, IMDG, IATA****Class** Void**14.4 Packing group****ADR, IMDG, IATA** Void

(Contd. on page 8)

**Material Safety Data Sheets**  
 according to 1907/2006/EC, Article 31

Printing date 23.05.2018

Version number 2

Revision: 13.12.2017

**Trade name: Osmo Oil Stain**

(Contd. of page 7)

<b>14.5 Environmental hazards:</b>	
<b>Marine pollutant:</b>	No
<b>14.6 Special precautions for user</b>	Not applicable.
<b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
<b>Transport/Additional information:</b>	Not dangerous according to the above specifications.
<b>UN "Model Regulation":</b>	Void

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulations:****GISBAU-Code**

GISCODE: Ö60

**VOC (EC)**

&lt; 500 g/l (VOC-max. = 500 g/l (2010 A/i))

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Relevant phrases**

H304 May be fatal if swallowed and enters airways.

**Department issuing SDS:**

product safety department

**Contact:**

Hr. Dr. Starp

**Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 IATA: International Air Transport Association  
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 Asp. Tox. 1: Aspiration hazard – Category 1