



The following technical datasheet is provided by Fein.

For further information please either give us a call or visit the manufacturer's website.

Wood Floors and Accessories cannot be held liable for the information contained within this document.
All information is correct at the time of download from the manufacturer.

Spilsby Road • Harold Hill • Romford • RM3 8SB • **T** 020 8501 6730 • **E** info@wfa.uk.net • **W** www.wfa.uk.net

Registered in England under Company No: 03746590 VAT No: 765 9995 45



MULTIMASTER MM 500 Plus

Oscillating multi-tool – MM 500

The powerful MultiTool for rapid work progress (in interior work and renovation) with a bimetal saw blade for wood, metal and plastics.

Product number: 7 229 67 62 24 1

Details

- › Anti-vibration system: continuously safe and pleasant working thanks to minimal vibrations and outstanding noise insulation.
- › StarlockPlus tool mounting: more work progress and greater precision thanks to 100% power transmission without losses.
- › QuickIN: tool changes in less than 3 seconds thanks to the patented tool-free FEIN rapid clamping system.
- › With the StarlockPlus tool mounting, you can access around 100 FEIN accessories from the Starlock and StarlockPlus performance classes.
- › 350 W FEIN motor. Powerful motor with a high copper content, which is suited to overload for a higher cutting speed and faster work progress.
- › Tacho generator: constant speeds even under load and infinitely variable electronic speed control.
- › Metal gearbox: ability to withstand high loading and outstanding service life because all the gearbox parts are made from metal.
- › Mechanical interface: for stationary operation in the table or drill jig holder or for securing the depth stop.
- › Industrial cable: large working radius thanks to finely stranded 5 metre rubber cable of industrial quality.

Price includes

- ✓ 1 Universal E-Cut saw blade (44 mm)
- ✓ 1 plastic carrying case

Product feature

- ✓ Mechanical interface

Technical data

TECHNICAL DATA

Input	350 W
Oscillations	10,000 - 19,500 rpm
Tool Holder	StarlockPlus
Tool change	QuickIN
Amplitude	2 x 1,7°
Cable with plug	5 m
Weight according to EPTA	1.40 kg

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Uncertainty of measured value KpA	72 dB 3 dB
Sound power level LWA Uncertainty of measured value KWA	83 dB 3 dB
Sound peak value LpCpeak Uncertainty of measured value KpCpeak	84 dB 3 dB

Application examples

