

# Product Data Sheet

## Stability Engineered Chevron - Finish BF808




Image shows Rustic option.

Should you require the information on any other details please contact the sales team on **020 8501 6730** or [info@wfa.uk.net](mailto:info@wfa.uk.net)

**MADE IN BRITAIN**



### Product Details

|               |  |
|---------------|--|
| Wood Species: | European Oak                                     |
| Construction: | Engineered                                       |
| Product Type: | Chevron 45° ^                                    |
| Grade:        | Prime / Rustic                                   |
| Profile:      | Tongue & Grooved with Left & Right Ends          |
| Edge Profile: | 1.50mm 4 Sided Micro Bevel                       |
| Finish:       | BF808 UV Oiled - Reactive Stain Bespoke Oil Silk |

|                      |                               |
|----------------------|-------------------------------|
| Product Description: | Stability 10                  |
| Total Thickness:     | <b>10mm</b>                   |
| Size/s:              | 500 x 90mm                    |
| Wear Layer:          | 4mm Oak Wear Layer            |
| Core Layer:          | 6mm Multi Layer Birch Plywood |

|                      |                                |
|----------------------|--------------------------------|
| Product Description: | Stability 15                   |
| Total Thickness:     | <b>15mm</b>                    |
| Size/s:              | 500 x 90mm / 600 x 120mm       |
| Wear Layer:          | 4mm Oak Wear Layer             |
| Core Layer:          | 11mm Multi Layer Birch Plywood |

|                      |                                |
|----------------------|--------------------------------|
| Product Description: | Stability 20                   |
| Total Thickness:     | <b>20mm</b>                    |
| Size/s:              | 500 x 90mm / 600 x 120mm       |
| Wear Layer:          | 6mm Oak Wear Layer             |
| Core Layer:          | 14mm Multi Layer Birch Plywood |

**NOTE:** Sizes shown in red are non stock items, delivery will be 7 - 10 weeks, subject to finish.

^ Alternative angles and sizes are available on request.

### Technical Information - Birch Plywood

|                             |  |
|-----------------------------|--|
| Country of Manufacture:     | Europe   |
| FSC®:                       | FSC 100% FSC-C111710   |
| Lamination:                 | Hydraulic Cold Press   |
| Glue Line:                  | D3 Water Based Glue  |
| Norm:                       | EN 14342:2013  |
| Reaction to Fire:           | 10mm & 15mm Dfl-s1 / 20mm Cf-s1                                |
| Density:                    | 650 kg/m <sup>3</sup>  |
| Formaldehyde Emissions:     | Class E1 Zero Emissions  |
| Warmth Conduction (approx): | 10mm – 0.074 W/m K<br>15mm – 0.111 W/m K<br>20mm – 0.148 W/m K |
| Production Tolerances;      |  |
| Width:                      | +/- 0.2mm  |
| Thickness (Above T&G):      | +/- 0.2mm  |
| Length:                     | +/- 0.2mm  |
| 90° Angle:                  | +/- 0.3°   |

### Grading

#### PRIME

|                               |                                |
|-------------------------------|--------------------------------|
| Maximum Size of Sound Knots:  | Possible knots up to 10mm      |
| Maximum Size of Filled Knots: | Possible knots up to 5mm       |
| Filled Defects:               | Not Allowed                    |
| Sap Wood:                     | Minimal Edge and Core Sap Wood |
| Colour Variation:             | Natural Variation Allowed      |
| Grain Variation:              | Mixture of Natural Grain       |

#### RUSTIC

|                               |                                    |
|-------------------------------|------------------------------------|
| Maximum Size of Sound Knots:  | Up to 70mm                         |
| Maximum Size of Filled Knots: | Up to 35mm                         |
| Filled Defects:               | Allowed                            |
| Filled Type:                  | Coloured Filler                    |
| Sap Wood:                     | Minimal Edge and Core Sap Wood     |
| Cracks:                       | Possible                           |
| Colour Variation:             | Natural Variation Allowed          |
| Grain Variation:              | Mixture of Natural Grain and Knots |

# Product Data Sheet

## Stability 20 Engineered Chevron - Finish BF808




Image shows Rustic option.

Should you require the information on any other details please contact the sales team on **020 8501 6730** or [info@wfa.uk.net](mailto:info@wfa.uk.net)

**MADE IN BRITAIN**



### Installation

Installation Method:                      Glued      Nailed      Floated on Underlay

**Please also refer to our guidelines.**                      ✓

NOTE: The fully bonded method of installation is recommended.

**Over Underfloor Heating:** When glued to an appropriate subfloor this product is suitable for use with water and some electric systems. Floor probes must be installed to control and regulate the flooring temperature which must not exceed 27°C. We also highly recommend the installation of a data recording Fidbox which measures and logs the temperature and humidity levels, see the data sheet for more information or [www.floorprotector.at](http://www.floorprotector.at)

**Site Conditions:** 45 – 65% relative humidity & 15 – 25°C room temperature.

Throughout the life of the floor, we recommend that the temperature should be maintained between 15°C and 25°C, and relative humidity levels between 45% and 65%, which will keep any movement within the floor to a minimum and ensure that the floor remains stable. As with any wooden floor, if humidity levels rise or fall outside of these parameters, a greater degree of shrinkage or expansion would be expected to occur.

For the complete installation guidelines please visit [www.wfa.uk.net](http://www.wfa.uk.net)

### Maintenance Advice

To fully aid in the care of the floor it is advised that all precautions are carried out. Avoid scratches by minimising grit and dust, install doorway entrance mats and apply felt pads to furniture. Use PH neutral cleaners and avoid soaking the floor with water at all times.

| Recommended Products  | Initial | Regular | Monthly | Long Term |
|-----------------------|---------|---------|---------|-----------|
| Sweep / Vacuum:       | ✓       | ✓       |         |           |
| <b>Oiled Finish</b>   |         |         |         |           |
| Osmo Wash and Care:   |         | ✓       |         |           |
| Osmo Maintenance Oil: |         |         |         | ✓         |

For the complete maintenance guidelines please visit [www.wfa.uk.net](http://www.wfa.uk.net)



Wood Floors & Accessories Limited guarantees to investigate any complaints reported within 25 years from the date of your sales invoice. In the event of a valid claim, Wood Floors & Accessories Limited will provide replacement material free of charge.

The lifetime of our guarantee covers the structural integrity of the product being the lamination, production, dimensions and grading.

For pre-finished floors our guarantee also covers that the surface finish will adhere correctly to the boards. It is however essential that a preventative cleaning and maintenance program is in use as set out in clause 4 & 5 of our [terms and conditions](#).

Wood is a natural product and will expand and contract throughout the four seasons. During these seasons, you may experience some natural movement which is not a product defect and is not covered by this guarantee.

As a general guideline, the ambient room temperature should be maintained between 15 and 25°C and humidity levels between 45 and 65%. To maintain these humidity levels, we would recommend using a humidifier/dehumidifier. Our guarantee is subject to your room conditions being maintained in accordance with British Standards current recommendations.

**All complaints are to be reported in writing by post or email to [info@wfa.uk.net](mailto:info@wfa.uk.net) within 48 hours of the issue becoming visible, to allow us to investigate the cause and extent of the problem.**