

# Product Data Sheet

## Genuine Reclaimed Oak Chevron Natural Oiled Rustic



Should you require the information on any other details please contact the sales team on **020 8501 6730** or [info@wfa.uk.net](mailto:info@wfa.uk.net)

**MADE IN BRITAIN**



### Product Details

Product Description:	Genuine Reclaimed Oak
Wood Species:	European Oak
Construction:	Engineered
Product Type:	Chevron 60°
Grade:	Rustic
Total Thickness:	17.5mm
Width:	100mm
Length:	600mm
Wear Layer:	5.5mm Oak Wear Layer
Core Layer:	12mm Multi Layer Birch Plywood
Profile:	Tongue & Grooved
Edge Profile:	4 Sided Micro Bevelled
Finish:	Heavy Brushed - Natural UV Oiled

### Technical Information

Country of Manufacture:	Europe
FSC®:	FSC MIX Credit FSC-C111710
Lamination:	Hydraulic Cold Press
Glue Line:	D3 Water Based Glue
Norm:	EN 13227
Reaction to Fire:	EN 13501-1 Dfl-S2
Density:	710 - 735 kg/m <sup>3</sup>
Formaldehyde Emissions:	Class E1 Zero Emissions
Warmth Conduction (approx):	0.130 - 0.140 W/m K
Production Tolerances;	
Width:	+/- 0.20mm
Thickness (Total):	+/- 0.20mm
Length:	+/- 0.20mm
90° Angle:	+/- 0.05°

**Guarantee:** 25 years; The lifetime of our guarantee covers the structural integrity of the product being the lamination, production, dimensions and grading. Please see our guarantee sheet for full details.

### Grading

Maximum Size of Sound Knots:	Unlimited
Maximum Size of Filled Knots:	Filled to maximum 60 – 70 mm Larger knots are cut off
Filled Defects:	Allowed
Filled Type:	Black Filler
Sap Wood:	Minimal Edge and Core Sap Wood
Colour Variation:	Natural Variation Allowed
Character Variation:	Original Bandsawn and Planer Marks with Irregular Edges Allowed
Grain Variation:	Mixture of Natural Grain, Open Splits, Holes, Knots, and Dead Worm Holes

### Installation

Installation Method:                      Glued      Nailed      Floated on Underlay

*Please also refer to our guidelines.*                      ✓                      ✓

NOTE: The fully bonded method of installation is recommended.

**Over Underfloor Heating:** When glued to an appropriate subfloor this product is suitable for use with water and some electric systems. Floor probes must be installed to control and regulate the flooring temperature which must not exceed 27°C. We also highly recommend the installation of a data recording Fidbox which measures and logs the temperature and humidity levels, see the data sheet for more information or [www.floorprotector.at](http://www.floorprotector.at)

**Site Conditions:** 45 – 65% relative humidity & 15 – 25°C room temperature.

### Maintenance Advice

To fully aid in the care of the floor it is advised that all precautions are carried out. Avoid scratches by minimising grit and dust, install doorway entrance mats and apply felt pads to furniture. Use PH neutral cleaners and avoid soaking the floor with water at all times.

Recommended Products	Initial	Regular	Monthly	Long Term
Sweep / Vacuum:	✓	✓		

### Oiled Finish

Osmo Wash and Care:	✓			
Osmo Maintenance Oil:				✓



Irregular edges



Bandsawn



Partially filled cracks



Partially filled knots



Woodworm\* and sapwood

© This technical data sheet was written by Wood Floors and Accessories Limited. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The images used on this sheet are for guidance purposes only. No rights can be derived from them. **Installation and Warranty:** The Wood Floors and Accessories warranty only applies to floors that have been installed by a competent flooring installer with the skills and knowledge to take into account individual site circumstances. This is in accordance with and comparable to BS 8201:2011 in the UK or equivalent standards worldwide.

\*Please note that ALL woodworm is no longer alive.

Wood Floors & Accessories Limited

Spilsby Road • Harold Hill • Romford • RM3 8SB

T 020 8501 6730 • E [info@wfa.uk.net](mailto:info@wfa.uk.net) • W [www.wfa.uk.net](http://www.wfa.uk.net)